

# Certificate of Accreditation

<b>Name of product:</b>	CertainTeed Asphalt Shingle Systems
<b>Product description:</b>	Roof Shingle System
<b>Description of the purpose and use of the building product:</b>	Roof cladding for structural reliability and weatherproofing purposes
<b>Regulation/s in relation to which the building product is accredited:</b>	<p>The Building Regulations Advisory Committee appointed under Division 4 of Part 12 of the Building Act 1993 has examined the application and accredited the product as complying with -</p> <p>Performance requirements relevant to the building product, as determined in accordance with the Building Code of Australia (BCA), NCC 2022 Volume One and Volume Two are B1P1, H1P1 regarding the structural performance of roof cladding in buildings, and F3P1, H2P2 regarding the weatherproofing performance of roof cladding in buildings.</p>
<b>Conditions to which the accreditation is subject:</b>	<ol style="list-style-type: none"><li>1. Installation is to be in accordance with Full Product Installation Manuals, including:<ul style="list-style-type: none"><li>• CertainTeed Shingle Applicator's Manual 12 - Landmark® Series</li><li>• Master Craftsman™ Shingle Applicator's Manual 10 – XT®-25</li><li>• Master Craftsman™ Shingle Applicator's Manual 11 – Landmark® Series</li><li>• Master Craftsman™ Shingle Applicator's Manual 14 – Presidential Shake® and Presidential Shake® TL</li><li>• Master Craftsman™ Shingle Applicator's Manual 15 – Highland Slate®</li><li>• Master Craftsman™ Shingle Applicator's Manual 16 - Belmont®</li><li>• Master Craftsman™ Shingle Applicator's Manual 17 – Grand Manor® and Carriage House®</li></ul></li><li>2. Minimum roof pitch 10 degrees, maximum roof pitch 75 degrees.<ol style="list-style-type: none"><li>a. For roof pitch of 10-60 degrees, Starter Strip shingles <b>must</b> be attached to the eave edge with four or five fasteners, equally spaced along the nail line.</li><li>b. For roof pitch greater than 60 degrees, Starter Strip shingles <b>must</b> be attached to the eave edge with four or five fasteners, equally spaced along the nail line. The Starter Strip shingles <b>must</b> overhang the eave and rake edges by 12.7 to 19.1 mm.</li></ol></li></ol>

# Building

## Regulations Advisory Committee

3. Where the roof pitch is 10 to 18 degrees, Flintlastic GTA-FR Membrane may be used in place of or in addition to the underlayment listed below.
4. The inclusion of either or a combination of the following underlayment:
  - a. Diamond Deck
  - b. Grace Select
  - c. Winterguard HT
  - d. Winterguard Sand
  - e. Winterguard Granular
  - f. Winterguard Metal
5. Roof framing system may vary as follows:
  - a. The framing may be arranged and specified to meet AS 1684 timber framing code or NASH standard – steel framed construction in a bushfire area.
  - b. Structural Plywood on roofing **must** be minimum 12mm thick F11 complying with AS/NZS 2269.
6. The shingle fixing shall be as specified in the relevant manual.
7. The inclusion of the following sealants in valleys, barges, hips, ridges and drip edges:
  - a. Bostik Seal “N” flex 1 polyurethane sealant (as tested) or polyurethane sealants such as Sikaflex-11 FC, Sikaflex Pro, Selleys Flexiseal FC, Selleys Flexiseal ProSeries, Tremco Polyroof LV.
  - b. One bead of sealant at these locations and to be fully covered by at least one layer of shingle.
8. Where valleys are included:
  - a. Valleys shall be covered by twice the layers of shingles as the rest of the roof with the underlayments listed above.

# Building

## Regulations Advisory Committee

**The name, address and Australian business number of the holder of the accreditation:** Shingle Roofing Systems of Australia Pty Ltd  
PO Box 171  
BROADFORD VIC 3658  
ACN: 005 084 668


**Certificate number:** V25/04

**Date of issue:** 16 July 2025

Refer to the Historical Details page of this Certificate.  
This Certificate is only valid when reproduced in its entirety.

**Date of expiry of accreditation:** 16 July 2028

**Signature:**



**Heidi Smith**  
Nominated Chair, Building Regulations Advisory Committee

### Practitioner guidance on how to use a Certificate of accreditation

Practitioners are reminded to consider any limitations noted in this Certificate and whether the performance of the product has been tested for all aspects of the performance that it is expected to achieve in the application it is being applied to.

This accreditation is only applicable for the State of Victoria.

Deemed to Satisfy solutions are not considered within the scope of this accreditation.

## Historical Details

Certificate number:	Description:	From:	To:
V25/04	Accreditation granted	16 July 2025	16 July 2028